

CARACTERISTICAS / FEATURES

Material hormigón Petra 1
Acabado decapado e hidrofugado
Dimensiones l. 155, a. 60, h. 85 cm
Color ver carta de colores
Fijación con varillas metálicas
Peso 875 kg
Palet 170 x 70 cm


Material precast concrete Petra 1
Finish scaled and waterproofed
Dimensions l.155, w.60, h. 85 cm
Colour see colour catalogue
Fixing with metal rods
Weight 875 kg
Pallet 170 x 70 cm

diseñador / design: Javier Gorostidi - Bernardo del Pino




BÉCQUER CONVEXO R.INT.14.7


GEOMETRIA / GEOMETRY



ALZADO FRONTAL / FRONT VIEW





PERFIL / PROFILE




PLANTA / TOP VIEW

ESC. 1:20


MANIPULACION E INSTALACION / HANDLING AND INSTALLATION



ESPECIFICACIONES / SPECIFICATIONS



PLANTA INFERIOR / BOTTOM VIEW



SECCION A-A'
SECTION A-A'


Encaje para luminaria LED
Socket for LED luminaire

Varilla roscada fijación M12 x 140
Threaded fixing rod M12 x 140

Sistema de fijación: a base cimentada taladrar pavimento Ø40 mm, rellenar con mortero rico o resina
Fixing system: to a cemented base drill pavement Ø40 mm, fill with rich mortar or resin


Casquillo roscado de elevación M12
Threaded fixing sleeve M12

Tornillo avellanado M12
Countersunk screw M12



DETALLE M / DETAIL M

Casquillo roscado de fijación M12
Threaded fixing sleeve M12



DETALLE N / DETAIL N